



The Compliance Department™

ALERT

MANAGEMENT BULLETIN

EPA NESHAP 6H Online Training

The EPA's National Emission Standards for Hazardous Air Pollutants (NESHAP) requires any employee that handles a spray gun to be certified every 5 years.



Great News! GMG EnviroSafe has an online certification that can complete the required training for your painters without them ever leaving the shop!

HOW IS IT COMPLETED?

Visit GMGEnviroSafe.com and select the NESHAP 6H Certification from the Services menu. Use the link to watch the training video and review proper spray gun set-up at your shop with your painters to minimize emissions.

Have each painter complete the Training Acknowledgment and answer the quiz questions. Then, submit the completed form to GMG EnviroSafe:

Email: documents@gmgenvirosafe.com
Fax: (847) 740-1635



WHAT HAPPENS NEXT?

If the painter passed the review quiz, GMG EnviroSafe will email a certificate of completion.

This certificate should be printed and placed in the NESHAP 6H folder of the DocuSystem (red compliance folders) and is good for 5 years.



QUESTIONS? CONTACT GMG ENVIROSAFE AT (800) 619-9733



A Division of Genesis Management Group, LTD.

1658 N Milwaukee Ave – Suite 287
Chicago, IL 60647
Phone: (800)619-9733 Fax: (847)740-1635
www.gmgenvirosafe.com



The Compliance Department™

ALERT

MANAGEMENT BULLETIN

EPA NESHAP 6H Training Acknowledgment

BY SIGNING BELOW, YOU ACKNOWLEDGE RECEIVING HANDS-ON AND CLASSROOM TRAINING ON THESE TOPICS:

NESHAP Regulatory Requirements
 Spray Gun Adjustments
 Spray Booth Filters

Spray Gun Selection
 Appropriate Spray Techniques
 Spray Booths & Prep Stations

Spray Gun Set-Up
 Spray Gun Cleaning
 Benefits of Compliance

Training Date _____	Shop Name _____	Shop Address _____
Painter Name (Print Legibly) _____	Painter Signature _____	

LIST THE DETAILS OF THE SPRAY GUNS THAT YOU USE IN THE SHOP

	Spray Gun Manufacturer	Spray Gun Model Number	Type	Max Input PSI
1			<input type="checkbox"/> HVLP	
2			<input type="checkbox"/> HVLP	
3			<input type="checkbox"/> HVLP	

CIRCLE YOUR ANSWERS FOR EACH OF THE REVIEW QUESTIONS AT THE END OF THE TRAINING HANDBOOK

Question 1	Question 2	Question 3	Question 4	Question 5
True	True	True	True	True
False	False	False	False	False
Question 6	Question 7	Question 8	Question 9	Question 10
True	True	True	True	True
False	False	False	False	False

SUBMIT THIS FORM FOR YOUR CERTIFICATE

EMAIL: DOCUMENTS@GMGENVIROSAFE.COM

FAX: (847) 740-1635





*The Compliance
Department™*

ALERT

MANAGEMENT BULLETIN

EPA NESHAP 6H Review Quiz

FOR EACH STATEMENT BELOW, CIRCLE YOUR ANSWER ON THE TRAINING ACKNOWLEDGMENT FORM.

1. NESHAP is the EPA's attempt to reduce Hazardous Air Pollutants (HAPs) emitted by the collision industry.
2. The distance between the spray gun and the coating surface will not affect transfer efficiency.
3. HVLP spray guns have an 85% transfer efficiency.
4. Spray coating can be done outdoors if an HVLP spray gun is used.
5. Air input, fluid flow, and fan adjustment are the main spray gun adjustments that can be made.
6. A spray gun should never be cleaned by spraying solvent.
7. When refinishing bare metal, you should apply primer only to the area needing repair and avoid overlap.
8. Following 6H NESHAP regulations will result in better health and safety for employees in the shop.
9. Mixing only the amounts of material needed will reduce paint cost and minimize air pollutants.
10. 6H NESHAP training requirements and practices apply to any employee who sprays material in the shop.

GMG EnviroSafe